

FEMALE PLUG
SCREWLESS

CONNETTORI FEMMINA
MOLLA


CONNECTEURS FEMELLE
RESSORT

STECKERTEIL
FEDERKRAFT

Pitch Pas	Passo Rastermaß	mm
Rated Voltage Tensione nominale	Tensione nominale Bemessungsspannung	V
Rated Current Intensité nominale	Corrente nominale Bemessungsstrom	A
Types of cables Type du conducteur	Tipo cavi Leitungstypen	
Nominal cross section Section nominale	Sezione nominale Nennquerschnitt	mm² AWG
Stripping lenght Longueur de dénudage	Lunghezza spelatura Abisolierlänge	mm
Temperature Température	Temperatura Temperatur	°C
Housing Corps isolant	Corpo isolante Isolierkörper	

	IMQ	EN61984
	VDE	EN61984
	cUL	UL1059 + C22.2 n°158
Poles Pôles	Poli Polzahl	X
Colours Couleurs	Colori Farben	Y

How to order Référence de commande	Ordinazione Bestellschlüssel
MRT48 P3,5 / X ... Y N...	
Type Pitch Poles Version Colors Printing	
Tipo Passo Poli Versione Colori Numerazione	
Type Pas Pôles Version Couleurs Marquage	
Typ Rastermaß Polzahl Version Farben Bedruckung	




Ta MAX: Max Ambient Temperature to perform nominal values
ULT: Upper Limit Temperature

MRT48

Single block · Blocco unico
Monobloc · Einzelblock


Poles · Poli · Pôles · Polzahl

2/20



3,5		
150		
8		
		
0,2 ÷ 1,5 26 ÷ 16	0,2 ÷ 1,5 26 ÷ 16	0,2 ÷ 1,5 26 ÷ 16
8		
Ta MAX: 75 / ULT: 160		
PA - UL 94 V0		

V	A	mm²/AWG
150	8	0,2 ÷ 1,5
300	8	26 ÷ 16
min 2 - max 20		
VE / on demand GR GR1 NE AR BL RO GI		



Version
Versione
...


P	L (mm)
3,5	3,5 x p

MRT48..FV

Single block · Blocco unico
Monobloc · Einzelblock

Poles · Poli · Pôles · Polzahl


2/20



3,5		
150		
8		
		
0,2 ÷ 1,5 26 ÷ 16	0,2 ÷ 1,5 26 ÷ 16	0,2 ÷ 1,5 26 ÷ 16
8		
Ta MAX: 75 / ULT: 160		
PA - UL 94 V0		

V	A	mm²/AWG
150	8	0,2 ÷ 1,5
300	8	26 ÷ 16

min 2 - max 20								
VE	/ on demand	GR	GR1	NE	AR	BL	RO	GI



Version
Versione
FV

P	L (mm)	X
3,5	(3,5 x p)+10,3	4,3