



FUSEHOLDER BLOCKS FOR P.C.B.
PORTAFUSIBILI NON PROTETTI PER C.S.



PTF/18 SMD (LCP)

Ordering codes:
PTF/18SMDV82NE
w/o hole in plastic body



PTF/18SMDV84NE
with hole in plastic body

Housing / Corpo isolante	High Temperature Thermoplastic LCP UL 94V-0
Solderability / Saldabilità	Reflow - 260 °C / 30 sec. max acc. to J-STD-020-D
Admissible ambient air temperature / Temperatura ambiente ammissibile	-30 °C to 85 °C
Shocksafe category / Protezione contro le scosse elettriche	PC1
Degree of protection / Grado di protezione	IP00 / IP20
Contact Resistance / Resistenza di contatto	< 5 mΩ

 EN 60127-6

Rated Current / Corrente Nominale	10 A
Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	4 W

 US UL 4248-1 + C22.2 no. 4248-1

Rated Current / Corrente Nominale	20 A
Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	—

Standard colour / Colore standard	Black / Nero
Other colours / Altri colori	—
Accessories / Accessori	Cover / Cappuccio BS613 p. 36
Other information / Altri dati	p. 39
Standard package / Imballo	Bulk / Scatola 1000 pcs T&R Ø380 mm - 400 pcs

