

SHOCKSAFE FUSEHOLDERS FOR PANEL
PORTAFUSIBILI PROTETTI DA PANNELLO

PTF/35



Fuse link / Fusibile tipo	5x20 mm
Mounting / Montaggio	Panel / Pannello
Rated Current / Corrente nominale	10 A
Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	2,5 W

Housing / Corpo isolante	Thermoplastic UL 94 V0
Admissible ambient air temperature / Temperatura ambiente ammissibile	-30 °C to 85 °C
Shocksafe category / Protezione contro le scosse elettriche	PC2
Degree of protection / Grado di protezione	IP40
Contact Resistance / Resistenza di contatto	< 5 mΩ

 EN 60127-6

Rated Current / Corrente Nominale	10 A
Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	2,5 W

 US UL 4248-1 + C22.2 no. 4248-1

Rated Current / Corrente Nominale	20 A
Rated Voltage / Tensione nominale	250 VAC
Rated Power Acceptance / Potenza dissipabile	—

Standard colour / Colore standard	Black / Nero
Other colours / Altri colori	On demand / A richiesta
Accessories / Accessori	—
Other information / Altri dati	p. 42
Standard package / Imballo	Bulk / Scatola 1000 pcs

